

Importing and exporting data in to and out of Cheddar (0.1-613)

Lawrence Hudson

2012-07-16

Contents

1	Introduction	1
2	Importing a single community from CSV data	1
2.1	properties.csv	2
2.2	nodes.csv	2
2.3	trophic.links.csv	3
2.4	Loading the community	3
3	Importing a collection of communities	6
4	Export	7
4.1	igraph	7
4.2	NetIndices	7

1 Introduction

Cheddar's `LoadCommunity` and `SaveCommunity` functions provide a standard data format for community representation. Data are stored in CSV (Comma-Separated Value) files, which are easily edited using standard software and are well supported by R. You should read the 'Community' vignette before reading this one.

Researchers typically use their own bespoke data formats. This means that there are probably as many data formats as there are researchers! It is therefore extremely hard to write a generic 'import my data in to Cheddar' function. Help is at hand! If you have community data that you would like to import in to Cheddar, please contact me (lawrence.hudson08 (at) imperial.ac.uk) - I will either provide example data-import R code for you to modify or will write the required R code for you.

2 Importing a single community from CSV data

A Cheddar community is represented by three files, each contains data for a different aspect of the community (Table 1). You can add properties to any aspect of the community simply by adding columns to the relevant CSV file. All properties added to these files are available to Cheddar's plotting and analysis functions. The following sections show how to import a community in to Cheddar using these three files and the `LoadCommunity` function. The data are from a fictitious community named 'Stream 12'.

Aspect	File	Description
Whole-community	properties.csv	Contains properties applicable to the community
Nodes	nodes.csv	Defines species and associated properties
Trophic Links	trophic.links.csv	Optional file that defines the food web

Table 1: Community files

2.1 properties.csv

This file must contain one row of data only (Table 2). This file must contain the ‘title’ column. The

title	M.units	N.units
Stream 12	kg	m ⁻²

Table 2: Example **properties.csv** file

‘M.units’ and/or ‘N.units’ must be present if the **properties.csv** file contains columns called ‘M’ and/or ‘N’. The contents of this file can be accessed using the **CPS** function, which returns a **list**.

2.2 nodes.csv

This file contains one row for every species in the community (Table 3). The ‘node’ column is the only

node	category	functional.group	M	N
Detritus		detritus		
Fungi		decomposer		
Species 1	producer	producer	3e-13	2e+06
Species 2	producer	producer	1e-13	3e+07
Species 3	producer	producer	7e-11	2e+07
Species 4	invertebrate	detritivore	4e-08	6e+06
Species 5	invertebrate	herbivore	6e-07	6e+05
Species 6	invertebrate	herbivore	1e-07	5e+06
Species 7	invertebrate	predator	9e-05	1e+07
Species 8	vert.ecto	predator	7e-03	2e+03

Table 3: Example **nodes.csv** file

mandatory column; all of the others are optional. The column ‘node’ must contain node names. An error is raised if any node names are duplicated. Whitespace is stripped from the beginning and end of node names. If provided, columns called ‘M’ and/or ‘N’ must represent mean body mass and mean numerical abundance respectively. All values in ‘M’ and ‘N’ must be either empty or greater than 0 and less than infinity. If the columns ‘M’ and/or ‘N’ are given then values named ‘M.units’ and/or ‘N.units’ must be

provided in the `properties.csv` file. The contents of this file can be accessed using the `NPS` function, which returns a `data.frame`.

Many of Cheddar's plot and analysis functions make use of the 'category' node property by default, following previously-used metabolic groupings (Yodzis and Innes, 1992). The 'category' column of `nodes.csv` is optional but, if given, it should contain one of 'producer', 'invertebrate', 'vert.ecto', 'vert.endo' or should be empty. The 'Detritus' and 'Fungi' nodes do not have a metabolic category so have no value for the 'category' column. The 'functional group' column contains a different way of classifying nodes in the community.

2.3 trophic.links.csv

This file contains a row for every resource-consumer trophic interaction in the community (Table 4). Values

resource	consumer
Detritus	Species 4
Detritus	Species 5
Fungi	Species 4
Fungi	Species 6
Species 1	Species 5
Species 1	Species 6
Species 2	Species 4
Species 2	Species 5
Species 2	Species 6
Species 3	Species 4
Species 3	Species 5
Species 3	Species 6
Species 4	Species 7
Species 4	Species 8
Species 5	Species 7
Species 6	Species 8
Species 7	Species 7
Species 7	Species 8

Table 4: Example `trophic.links.csv` file

in 'resource' and 'consumer' should contain node names. An error is raised if any names in 'resource' or 'consumer' are not in the 'node' column of the `nodes.csv` file. Whitespace is stripped from the beginning and end of all values in 'resource' and 'consumer'. Other columns are properties of trophic links. An error is raised if any links appear more than once. The contents of this file can be accessed using the `TLPS` function, which returns a `data.frame`.

2.4 Loading the community

The above files should be in the same directory, say '`c:/Stream12`'.

```
> stream12 <- LoadCommunity('c:/Stream12')
```

Examine the community to make sure that the data have been imported correctly.

```
> stream12
```

Stream 12 containing 10 nodes.

```
> NumberOfNodes(stream12)
```

```
[1] 10
```

```
> NumberOfTrophicLinks(stream12)
```

```
[1] 18
```

Examine each of the three aspects.

```
> # Community properties
```

```
> CPS(stream12)
```

```
$title
```

```
[1] "Stream 12"
```

```
$M.units
```

```
[1] "kg"
```

```
$N.units
```

```
[1] "m^-2"
```

```
> # Node properties
```

```
> NPS(stream12)
```

	node	category	functional.group	M	N
Detritus	Detritus		detritus	NA	NA
Fungi	Fungi		decomposer	NA	NA
Species 1	Species 1	producer	producer	3e-13	2e+06
Species 2	Species 2	producer	producer	1e-13	3e+07
Species 3	Species 3	producer	producer	7e-11	2e+07
Species 4	Species 4	invertebrate	detritivore	4e-08	6e+06
Species 5	Species 5	invertebrate	herbivore	6e-07	6e+05
Species 6	Species 6	invertebrate	herbivore	1e-07	5e+06
Species 7	Species 7	invertebrate	predator	9e-05	1e+07
Species 8	Species 8	vert.ecto	predator	7e-03	2e+03

```
> # Trophic links
```

```
> TLPS(stream12)
```

	resource	consumer
1	Detritus	Species 4
2	Detritus	Species 5
3	Fungi	Species 4
4	Fungi	Species 6
5	Species 1	Species 5
6	Species 1	Species 6
7	Species 2	Species 4
8	Species 2	Species 5
9	Species 2	Species 6
10	Species 3	Species 4
11	Species 3	Species 5
12	Species 3	Species 6
13	Species 4	Species 7
14	Species 4	Species 8
15	Species 5	Species 7
16	Species 6	Species 8
17	Species 7	Species 7
18	Species 7	Species 8

SumBiomassByClass returns the total biomass in each 'category' node property.

```
> SumBiomassByClass(stream12)
```

	invertebrate	producer	vert.ecto
	0.0000e+00	9.0110e+02	1.4036e-03
			1.4000e+01

You can easily get the total biomass in each 'functional.group'.

```
> SumBiomassByClass(stream12, class='functional.group')
```

decomposer	detritivore	detritus	herbivore	predator	producer
0.0000e+00	2.4000e-01	0.0000e+00	8.6000e-01	9.1400e+02	1.4036e-03

3 Importing a collection of communities

Cheddar’s `LoadCollection` and `SaveCollection` functions provide a standard data format for collections of communities. Each community in a collection is stored in its own directory using the CSV format described in Section 2. For example, the following fictitious collection ‘Grassland1994’ contains three communities: ‘Plot 1’, ‘Plot 2’ and ‘Plot 3’.

```
Grassland1994
|
| - communities
|   |
|   | - Plot 1
|   |   |
|   |   | - nodes.csv
|   |   | - properties.csv
|   |   | - trophic.links.csv
|   | - Plot 2
|   |   |
|   |   | - nodes.csv
|   |   | - properties.csv
|   |   | - trophic.links.csv
|   | - Plot 3
|   |   |
|   |   | - nodes.csv
|   |   | - properties.csv
|   |   | - trophic.links.csv
```

The `LoadCommunity` function loads the collection in to R .

```
> grassland <- LoadCommunity('c:/Grassland1994')
```

```
> grassland
```

A collection of 3 communities

```
> length(grassland)
```

```
[1] 3
```

The ‘Collections’ vignette explains information community collections in detail.

4 Export

The `SaveCommunity` and `SaveCollection` functions export communities and collections respectively to CSV files.

4.1 igraph

The following function can be used to export a Cheddar community to the `igraph` package (Csardi and Nepusz, 2006).

```
> ToIgraph <- function(community, weight=NULL)
{
  if(is.null(TLPS(community)))
  {
    stop('The community has no trophic links')
  }
  else
  {
    ttps <- TLPS(community, link.properties=weight)
    if(!is.null(weight))
    {
      ttps$weight <- ttps[,weight]
    }
    return (graph.data.frame(ttps,
                             vertices=NPS(community),
                             directed=TRUE))
  }
}
> data(TL84)
> # Unweighted network
> TL84.ig <- ToIgraph(TL84)
> data(Benguela)
> # Use diet fraction to weight network
> Benguela.ig <- ToIgraph(Benguela, weight='diet.fraction')
```

4.2 NetIndices

The `PredationMatrix` function can be used to export a Cheddar community to the `NetIndices` package (Kones et al., 2009).

```
> data(TL84)
> # Unweighted network
> TL84.ni <- PredationMatrix(TL84)
> data(Benguela)
> # Use diet fraction to weight network
> Benguela.ni <- PredationMatrix(Benguela, weight='diet.fraction')
```

References

- Gabor Csardi and Tamas Nepusz. The igraph software package for complex network research. *InterJournal*, Complex Systems:1695, 2006. URL <http://igraph.sf.net>.
- Julius Kipyegon Kones, Karline Soetaert, Dick van Oevelen, and John Owino. Are network indices robust indicators of food web functioning? a monte carlo approach. *Ecological Modelling*, 220:370–382, 2009. doi: 10.1016/j.ecolmodel.2008.10.012.
- Peter Yodzis and Stuart Innes. Body size and resource-consumer dynamics. 139(6):1151–1175, 1992. doi: 10.1086/285380.