

# iemisc: Examples from GNU Octave Rem, Mod, and fractdiff Compatible Functions

Irucka Embry, E.I.T. (EcoC<sup>2</sup>S)

2023-03-03

## Contents

<b>Rem Examples (R style)</b>	<b>1</b>
<b>rem Examples (GNU Octave style)</b>	<b>2</b>
<b>Mod_octave Examples (R style)</b>	<b>4</b>
<b>mod Examples (GNU Octave style)</b>	<b>5</b>
<b>fractdiff Example (R style)</b>	<b>6</b>
<b>fractdiff Example (GNU Octave style)</b>	<b>6</b>
Works Cited . . . . .	6
<b>EcoC<sup>2</sup>S Links</b>	<b>7</b>
<b>Copyright and License</b>	<b>7</b>

## Rem Examples (R style)

```
library("iemisc")

# Examples from GNU Octave

x <- 23.4
y <- 20
z <- 0

Rem(x, y)

## [1] 3.4
Rem(y, x)

## [1] 20
Rem(x, z)

## [1] NaN
```

```

Rem(y, z)

## [1] NaN
Rem(z, x)

## [1] 0
Rem(z, y)

## [1] 0
Rem(-1, 3)

## [1] -1
# Examples from FreeMat

Rem(18, 12)

## [1] 6
Rem(6, 5)

## [1] 1
Rem(2 * pi, pi)

## [1] 0
Rem(c(1, 3, 5, 2), 2)

##      [,1] [,2] [,3] [,4]
## [1,]    1    1    1    0
Rem(c(9, 3, 2, 0), c(1, 0, 2, 2))

## [1]    0 NaN    0    0

```

## rem Examples (GNU Octave style)

```

% check against GNU Octave

% Examples from GNU Octave

x = 23.4

y = 20

z = 0

rem(x, y)

rem(y, x)

rem(x, z)

```

```

rem(y, z)

rem(z, x)

rem(z, y)

rem(-1, 3)

% Examples from FreeMat

rem(18, 12)

rem(6, 5)

rem(2 * pi, pi)

rem([1, 3, 5, 2], 2)

rem([9 3 2 0], [1 0 2 2])

% results

>> x = 23.4
x = 23.400
>>
>> y = 20
y = 20
>>
>> z = 0
z = 0
>>
>> rem(x, y)
ans = 3.4000
>>
>> rem(y, x)
ans = 20
>>
>> rem(x, z)
ans = NaN
>>
>> rem(y, z)
ans = NaN
>>
>> rem(z, x)
ans = 0
>>
>> rem(z, y)
ans = 0
>>
>> rem(-1, 3)

```

```

ans = -1
>>
>>
>> % Examples from FreeMat
>>
>> rem(18, 12)
ans = 6
>>
>> rem(6, 5)
ans = 1
>>
>> rem(2 * pi, pi)
ans = 0
>>
>> rem([1, 3, 5, 2], 2)
ans =

    1    1    1    0

>>
>> rem([9 3 2 0], [1 0 2 2])
ans =

    0   NaN    0    0

>>

```

## Mod\_octave Examples (R style)

```

library("iemisc")

# Examples from FreeMat

Mod_octave(6, 5)

## [1] 1
Mod_octave(2 * pi, pi)

## [1] 0
Mod_octave(c(1, 3, 5, 2), 2)

##      [,1] [,2] [,3] [,4]
## [1,]    1    1    1    0
Mod_octave(c(9, 3, 2, 0), c(1, 0, 2, 2))

## [1] 0 3 0 0
Mod_octave(-1, 3)

## [1] 2

```

## mod Examples (GNU Octave style)

```
% check against GNU Octave
```

```
% Examples from FreeMat
```

```
mod(18, 12)
```

```
mod(6, 5)
```

```
mod(2*pi, pi)
```

```
mod([1, 3, 5, 2], 2)
```

```
mod([9 3 2 0], [1 0 2 2])
```

```
mod(-1, 3)
```

```
% results
```

```
>> mod(18, 12)
```

```
ans = 6
```

```
>>
```

```
>> mod(6, 5)
```

```
ans = 1
```

```
>>
```

```
>> mod(2*pi, pi)
```

```
ans = 0
```

```
>>
```

```
>> mod([1, 3, 5, 2], 2)
```

```
ans =
```

```
1 1 1 0
```

```
>>
```

```
>> mod([9 3 2 0], [1 0 2 2])
```

```
ans =
```

```
0 3 0 0
```

```
>>
```

```
>> mod(-1, 3)
```

```
ans = 2
```

```
>>
```

## fractdiff Example (R style)

```
library("iemisc")
import::from(ramify, mat)

# values from https://github.com/simaki/fractdiff

a <- mat("1, 2, 4, 7, 0")

fractdiff(x = a, d = 0.5)

## [1] 1.000000 1.500000 2.875000 4.687500 -4.164062
```

## fractdiff Example (GNU Octave style)

```
% check against GNU Octave

a = [1, 2, 4, 7, 0]

fractdiff(a, d = 0.5)

% results

>> a = [1, 2, 4, 7, 0]
a =

    1    2    4    7    0

>>
>> fractdiff(a, d = 0.5)
ans =

    1.0000    1.5000    2.8750    4.6875   -4.1641

>>
```

## Works Cited

John W. Eaton, David Bateman, Søren Hauberg, and Rik Wehbring (October 2021). *GNU Octave: A high-level interactive language for numerical computations: Edition 6 for Octave version 6.4.0*. <https://www.gnu.org/software/octave/octave.pdf>. Page 547.

## EcoC<sup>2</sup>S Links

EcoC<sup>2</sup>S Home – <https://www.ecoccs.com/>

About EcoC<sup>2</sup>S – [https://www.ecoccs.com/about\\_ecoc2s.html](https://www.ecoccs.com/about_ecoc2s.html)

Products – <https://www.questionuniverse.com/products.html>

EcoC<sup>2</sup>S Media – <https://www.ecoccs.com/media.html>

EcoC<sup>2</sup>S Resources – <https://www.ecoccs.com/resources.html>

R Trainings and Resources provided by EcoC<sup>2</sup>S (Iruka Embry, E.I.T.) – <https://www.ecoccs.com/rtraining.html>

## Copyright and License

All R code written by Iruka Embry is distributed under the GPL-3 (or later) license, see the [GNU General Public License {GPL}](#) page.

All written content originally created by Iruka Embry is copyrighted under the Creative Commons Attribution-ShareAlike 4.0 International License. All other written content retains the copyright of the original author(s).



This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](#).