

# Package ‘MKpower’

September 5, 2025

**Version** 1.1

**Date** 2025-09-05

**Title** Power Analysis and Sample Size Calculation

**Author** Matthias Kohl [aut, cre] (ORCID:  
<<https://orcid.org/0000-0001-9514-8910>>)

**Maintainer** Matthias Kohl <Matthias.Kohl@stamats.de>

**Depends** R(>= 3.5.0)

**Imports** stats, matrixTests(>= 0.2), ggplot2, MKdescr, MKinfer(>= 0.4),  
qqplotr, coin, mvtnorm, rlang

**Suggests** knitr, rmarkdown, hexbin

**VignetteBuilder** knitr

**Description** Power analysis and sample size calculation for Welch and Hsu (Hedderich and Sachs (2018), ISBN:978-3-662-56657-2) t-tests including Monte-Carlo simulations of empirical power and type-I-error. Power and sample size calculation for Wilcoxon rank sum and signed rank tests via Monte-Carlo simulations. Power and sample size required for the evaluation of a diagnostic test(-system) (Flahault et al. (2005), <[doi:10.1016/j.jclinepi.2004.12.009](https://doi.org/10.1016/j.jclinepi.2004.12.009)>; Dobbin and Simon (2007), <[doi:10.1093/biostatistics/kxj036](https://doi.org/10.1093/biostatistics/kxj036)>) as well as for a single proportion (Fleiss et al. (2003), ISBN:978-0-471-52629-2; Piegorsch (2004), <[doi:10.1016/j.csda.2003.10.002](https://doi.org/10.1016/j.csda.2003.10.002)>; Thulin (2014), <[doi:10.1214/14-ejs909](https://doi.org/10.1214/14-ejs909)>), comparing two negative binomial rates (Zhu and Lakkis (2014), <[doi:10.1002/sim.5947](https://doi.org/10.1002/sim.5947)>), ANCOVA (Shieh (2020), <[doi:10.1007/s11336-019-09692-3](https://doi.org/10.1007/s11336-019-09692-3)>), reference ranges (Jennen-Steinmetz and Wellek (2005), <[doi:10.1002/sim.2177](https://doi.org/10.1002/sim.2177)>), multiple primary endpoints (Sozu et al. (2015), ISBN:978-3-319-22005-5), and AUC (Hanley and McNeil (1982), <[doi:10.1148/radiology.143.1.7063747](https://doi.org/10.1148/radiology.143.1.7063747)>).

**License** LGPL-3

**URL** <https://github.com/stamats/MKpower>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2025-09-05 17:00:08 UTC

## Contents

|                                 |           |
|---------------------------------|-----------|
| MKpower-package . . . . .       | 2         |
| hist . . . . .                  | 3         |
| power.ancova . . . . .          | 4         |
| power.diagnostic.test . . . . . | 6         |
| power.hsu.t.test . . . . .      | 9         |
| power.mpe.atleast.one . . . . . | 11        |
| power.mpe.known.var . . . . .   | 12        |
| power.mpe.unknown.var . . . . . | 14        |
| power.nb.test . . . . .         | 16        |
| power.prop1.test . . . . .      | 18        |
| power.welch.t.test . . . . .    | 20        |
| print.power.mpe.test . . . . .  | 22        |
| qqunif . . . . .                | 23        |
| sim.power.t.test . . . . .      | 24        |
| sim.power.wilcox.test . . . . . | 27        |
| sim.ssize.wilcox.test . . . . . | 29        |
| ssize.auc.ci . . . . .          | 32        |
| ssize.pcc . . . . .             | 33        |
| ssize.propCI . . . . .          | 35        |
| ssize.reference.range . . . . . | 36        |
| volcano . . . . .               | 39        |
| <b>Index</b>                    | <b>42</b> |

---

MKpower-package

*Power Analysis and Sample Size Calculation.*

---

## Description

Power analysis and sample size calculation for Welch and Hsu (Hedderich and Sachs (2018), ISBN:978-3-662-56657-2) t-tests including Monte-Carlo simulations of empirical power and type-I-error. Power and sample size calculation for Wilcoxon rank sum and signed rank tests via Monte-Carlo simulations. Power and sample size required for the evaluation of a diagnostic test(-system) (Flahault et al. (2005), <doi:10.1016/j.jclinepi.2004.12.009>; Dobbin and Simon (2007), <doi:10.1093/biostatistics/kxj036>) as well as for a single proportion (Fleiss et al. (2003), ISBN:978-0-471-52629-2; Piegorsch (2004), <doi:10.1016/j.csda.2003.10.002>; Thulin (2014), <doi:10.1214/14-ejs909>), comparing two negative binomial rates (Zhu and Lakkis (2014), <doi:10.1002/sim.5947>), ANCOVA (Shieh (2020), <doi:10.1007/s11336-019-09692-3>), reference ranges (Jennen-Steinmetz and Wellek (2005), <doi:10.1002/sim.2177>), multiple primary endpoints (Sozu et al. (2015), ISBN:978-3-319-22005-5), and AUC (Hanley and McNeil (1982), <doi:10.1148/radiology.143.1.7063747>).

## Details

library(MKpower)

**Author(s)**

Matthias Kohl <https://www.stamats.de>

Maintainer: Matthias Kohl <matthias.kohl@stamats.de>

---

hist

*Histograms*

---

**Description**

Produce histograms for simulations of power and type-I-error of tests.

**Usage**

```
## S3 method for class 'sim.power.ttest'  
hist(x, color.hline = "orange", ...)  
  
## S3 method for class 'sim.power.wtest'  
hist(x, color.hline = "orange", ...)
```

**Arguments**

|             |                                                                       |
|-------------|-----------------------------------------------------------------------|
| x           | object of class <code>sim.power.ttest</code> .                        |
| color.hline | color of horizontal line indicating uniform distribution of p values. |
| ...         | further arguments that may be passed through).                        |

**Details**

The plot generates a `ggplot2` object that is shown.

Missing values are handled by the `ggplot2` functions.

**Value**

Object of class `gg` and `ggplot`.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**See Also**

[hist](#)

## Examples

```
res1 <- sim.power.t.test(nx = 5, rx = rnorm, rx.H0 = rnorm,
                        ny = 10, ry = function(x) rnorm(x, mean = 3, sd = 3),
                        ry.H0 = function(x) rnorm(x, sd = 3))

hist(res1)

res2 <- sim.power.wilcox.test(nx = 6, rx = rnorm, rx.H0 = rnorm,
                             ny = 6, ry = function(x) rnorm(x, mean = 2),
                             ry.H0 = rnorm)

hist(res2)
```

---

power.ancova

*Power Calculation for ANCOVA*

---

## Description

Compute sample size for ANCOVA.

## Usage

```
power.ancova(n = NULL, mu = NULL, var = 1, nr.covs = 1L, group.ratio = NULL,
             contr.mat = NULL, sig.level = 0.05, power = NULL, n.max = 1000L,
             rel.tol = .Machine$double.eps^0.25)
```

## Arguments

|             |                                                                                                                                                 |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| n           | vector of sample sizes per groups.                                                                                                              |
| mu          | vector of mean values of the groups.                                                                                                            |
| var         | error variance.                                                                                                                                 |
| nr.covs     | number of covariates (larger or equal than 1).                                                                                                  |
| group.ratio | vector of group sizes relative to group 1; i.e., first entry should always be one. If NULL, a balanced design is used.                          |
| contr.mat   | matrix of contrasts (number of columns must be identical to number of groups). If NULL, standard ANCOVA contrasts are used; see examples below. |
| sig.level   | significance level (type I error probability)                                                                                                   |
| power       | power of test (1 minus type II error probability)                                                                                               |
| n.max       | maximum sample size considered in the computations.                                                                                             |
| rel.tol     | relative tolerance passed to function integrate.                                                                                                |

## Details

Exactly one of the parameters n and power must be passed as NULL, and that parameter is determined from the other.

The function includes an implementation of the exact approach of Shieh (2020). It is based on the code provided in the supplement of Shieh (2020), but uses `integrate` instead of the trapezoid rule and `uniroot` for finding the required sample size.

**Value**

Object of class "power.htest", a list of the arguments (including the computed one) augmented with a note element.

**Author(s)**

Matthias Kohl <Matthias.Kohl@statamats.de>

**References**

G. Shieh (2020). Power Analysis and Sample Size Planning in ANCOVA Designs. *Psychometrika* **85**:101-120. doi:[10.1007/s11336019096923](https://doi.org/10.1007/s11336019096923).

S.E. Maxwell and H.D. Delaney (2004). *Designing experiments and analyzing data: A model comparison perspective* (2nd ed.). Mahwah, NJ: Lawrence Erlbaum Associates.

**See Also**

[power.anova.test](#), [power.t.test](#)

**Examples**

```
## Default matrix of contrasts
## 3 groups
cbind(rep(1,2), -diag(2))
## 4 groups
cbind(rep(1,3), -diag(3))

## Table 1 in Shieh (2020)
power.ancova(mu=c(400, 450, 500), var = 9900, power = 0.8)
power.ancova(n = rep(63/3, 3), mu=c(400, 450, 500), var = 9900)
power.ancova(mu=c(400, 450, 500), var = 9900, power = 0.8, nr.covs = 10)
power.ancova(n = rep(72/3, 3), mu=c(400, 450, 500), var = 9900, nr.covs = 10)

## Table 2 in Shieh (2020)
power.ancova(mu=c(400, 450, 500), var = 7500, power = 0.8)
power.ancova(n = rep(48/3, 3), mu=c(400, 450, 500), var = 7500)
power.ancova(mu=c(400, 450, 500), var = 7500, power = 0.8, nr.covs = 10)
power.ancova(n = rep(60/3, 3), mu=c(400, 450, 500), var = 7500, nr.covs = 10)

## Table 3 in Shieh (2020)
power.ancova(mu=c(400, 450, 500), var = 1900, power = 0.8)
power.ancova(n = rep(18/3, 3), mu=c(400, 450, 500), var = 1900)
power.ancova(mu=c(400, 450, 500), var = 1900, power = 0.8, nr.covs = 10)
power.ancova(n = rep(27/3, 3), mu=c(400, 450, 500), var = 1900, nr.covs = 10)

## ANOVA approach for Table 1-3
power.anova.test(groups = 3, between.var = var(c(400, 450, 500)),
                  within.var = 10000, power = 0.8)
power.anova.test(n = 63/3, groups = 3, between.var = var(c(400, 450, 500)),
                  within.var = 10000)
```

```

## Table 4 in Shieh (2020)
power.ancova(mu=c(410, 450, 490), var = 9900, power = 0.8)
power.ancova(n = rep(96/3, 3), mu=c(410, 450, 490), var = 9900)
power.ancova(mu=c(410, 450, 490), var = 9900, power = 0.8, nr.covs = 10)
power.ancova(n = rep(105/3, 3), mu=c(410, 450, 490), var = 9900, nr.covs = 10)

## Table 5 in Shieh (2020)
power.ancova(mu=c(410, 450, 490), var = 7500, power = 0.8)
power.ancova(n = rep(72/3, 3), mu=c(410, 450, 490), var = 7500)
power.ancova(mu=c(410, 450, 490), var = 7500, power = 0.8, nr.covs = 10)
power.ancova(n = rep(84/3, 3), mu=c(410, 450, 490), var = 7500, nr.covs = 10)

## Table 6 in Shieh (2020)
power.ancova(mu=c(410, 450, 490), var = 1900, power = 0.8)
power.ancova(n = rep(24/3, 3), mu=c(410, 450, 490), var = 1900)
power.ancova(mu=c(410, 450, 490), var = 1900, power = 0.8, nr.covs = 10)
power.ancova(n = rep(33/3, 3), mu=c(410, 450, 490), var = 1900, nr.covs = 10)

## ANOVA approach for Table 4-6
power.anova.test(groups = 3, between.var = var(c(410, 450, 490)),
  within.var = 10000, power = 0.8)
power.anova.test(n = 96/3, groups = 3, between.var = var(c(410, 450, 490)),
  within.var = 10000)

#####
## Example from Maxwell and Delaney (2004) according to Shieh (2020)
#####
## ANCOVA (balanced design)
power.ancova(n = rep(30/3, 3), mu=c(7.5366, 11.9849, 13.9785), var = 29.0898)
power.ancova(mu=c(7.5366, 11.9849, 13.9785), var = 29.0898, power = 0.8)
power.ancova(mu=c(7.5366, 11.9849, 13.9785), var = 29.0898, power = 0.9)

## ANOVA
power.anova.test(n = 30/3, groups = 3, between.var = var(c(7.5366, 11.9849, 13.9785)),
  within.var = 29.0898)
power.anova.test(groups = 3, between.var = var(c(7.5366, 11.9849, 13.9785)),
  within.var = 29.0898, power = 0.8)
power.anova.test(groups = 3, between.var = var(c(7.5366, 11.9849, 13.9785)),
  within.var = 29.0898, power = 0.9)

## ANCOVA - imbalanced design
power.ancova(mu=c(7.5366, 11.9849, 13.9785), var = 29.0898, power = 0.8,
  group.ratio = c(1, 1.25, 1.5))
power.ancova(n = c(13, 16, 19), mu=c(7.5366, 11.9849, 13.9785), var = 29.0898,
  group.ratio = c(1, 1.25, 1.5))
power.ancova(mu=c(7.5366, 11.9849, 13.9785), var = 29.0898, power = 0.8,
  group.ratio = c(1, 0.8, 2/3))
power.ancova(n = c(17, 14, 12), mu=c(7.5366, 11.9849, 13.9785), var = 29.0898,
  group.ratio = c(1, 0.8, 2/3))

```

## Description

Compute sample size, power, delta, or significance level of a diagnostic test for an expected sensitivity or specificity.

## Usage

```
power.diagnostic.test(sens = NULL, spec = NULL,
                      n = NULL, delta = NULL, sig.level = 0.05,
                      power = NULL, prev = NULL,
                      method = c("exact", "asymptotic"),
                      NMAX = 1e4)
ssize.sens.ci(sens = NULL, n = NULL, delta = NULL, sig.level = 0.05,
              power = NULL, prev = NULL, method = c("exact", "asymptotic"),
              NMAX = 1e4)
ssize.spec.ci(spec = NULL, n = NULL, delta = NULL, sig.level = 0.05,
              power = NULL, prev = NULL, method = c("exact", "asymptotic"),
              NMAX = 1e4)
```

## Arguments

|           |                                                                                       |
|-----------|---------------------------------------------------------------------------------------|
| sens      | Expected sensitivity; either sens or spec has to be specified.                        |
| spec      | Expected specificity; either sens or spec has to be specified.                        |
| n         | Number of cases if sens and number of controls if spec is given.                      |
| delta     | sens-delta resp. spec-delta is used as lower confidence limit                         |
| sig.level | Significance level (Type I error probability)                                         |
| power     | Power of test (1 minus Type II error probability)                                     |
| prev      | Expected prevalence, if NULL prevalence is ignored which means prev = 0.5 is assumed. |
| method    | exact or asymptotic formula; default "exact".                                         |
| NMAX      | Maximum sample size considered in case method = "exact".                              |

## Details

Either sens or spec has to be specified which leads to computations for either cases or controls.

Exactly one of the parameters n, delta, sig.level, and power must be passed as NULL, and that parameter is determined from the others. Notice that sig.level has a non-NULL default so NULL must be explicitly passed if you want to compute it.

The computations are based on the formulas given in the Appendix of Flahault et al. (2005). Please be careful, in Equation (A1) the numerator should be squared, in equation (A2) and (A3) the second exponent should be n-i and not i.

As noted in Chu and Cole (2007) power is not a monotonically increasing function in n but rather saw toothed (see also Chernick and Liu (2002)). Hence, in our calculations we use the more conservative approach II); i.e., the minimum sample size n such that the actual power is larger or equal power and such that for any sample size larger than n it also holds that the actual power is larger or equal power.

**Value**

Object of class "power.htest", a list of the arguments (including the computed one) augmented with method and note elements.

**Note**

uniroot is used to solve power equation for unknowns, so you may see errors from it, notably about inability to bracket the root when invalid arguments are given.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

A. Flahault, M. Cadilhac, and G. Thomas (2005). Sample size calculation should be performed for design accuracy in diagnostic test studies. *Journal of Clinical Epidemiology*, **58**(8):859-862.

H. Chu and S.R. Cole (2007). Sample size calculation using exact methods in diagnostic test studies. *Journal of Clinical Epidemiology*, **60**(11):1201-1202.

M.R. Chernick and C.Y. Liu (2002). The saw-toothed behavior of power versus sample size and software solutions: single binomial proportion using exact methods. *Am Stat*, **56**:149-155.

**See Also**

[uniroot](#)

**Examples**

```
## see n2 on page 1202 of Chu and Cole (2007)
power.diagnostic.test(sens = 0.99, delta = 0.14, power = 0.95) # 40
power.diagnostic.test(sens = 0.99, delta = 0.13, power = 0.95) # 43
power.diagnostic.test(sens = 0.99, delta = 0.12, power = 0.95) # 47

power.diagnostic.test(sens = 0.98, delta = 0.13, power = 0.95) # 50
power.diagnostic.test(sens = 0.98, delta = 0.11, power = 0.95) # 58

## see page 1201 of Chu and Cole (2007)
power.diagnostic.test(sens = 0.95, delta = 0.1, n = 93) ## 0.957
power.diagnostic.test(sens = 0.95, delta = 0.1, n = 93, power = 0.95,
  sig.level = NULL) ## 0.0496
power.diagnostic.test(sens = 0.95, delta = 0.1, n = 102) ## 0.968
power.diagnostic.test(sens = 0.95, delta = 0.1, n = 102, power = 0.95,
  sig.level = NULL) ## 0.0471
## yields 102 not 93!
power.diagnostic.test(sens = 0.95, delta = 0.1, power = 0.95)

## function only for sensitivity
ssize.sens.ci(sens = 0.99, delta = 0.14, power = 0.95) # 40

## function only for specificity
ssize.spec.ci(spec = 0.99, delta = 0.13, power = 0.95) # 43
```

---

power.hsu.t.test

---

*Power Calculations for Two-sample Hsu t Test*


---

## Description

Compute the power of the two-sample Hsu t test, or determine parameters to obtain a target power; see Section 7.4.4 in Hedderich and Sachs (2016).

## Usage

```
power.hsu.t.test(n = NULL, delta = NULL, sd1 = 1, sd2 = 1, sig.level = 0.05,
                 power = NULL, alternative = c("two.sided", "one.sided"),
                 strict = FALSE, tol = .Machine$double.eps^0.25)
```

## Arguments

|             |                                                                                                     |
|-------------|-----------------------------------------------------------------------------------------------------|
| n           | number of observations (per group)                                                                  |
| delta       | (expected) true difference in means                                                                 |
| sd1         | (expected) standard deviation of group 1                                                            |
| sd2         | (expected) standard deviation of group 2                                                            |
| sig.level   | significance level (Type I error probability)                                                       |
| power       | power of test (1 minus Type II error probability)                                                   |
| alternative | one- or two-sided test. Can be abbreviated.                                                         |
| strict      | use strict interpretation in two-sided case                                                         |
| tol         | numerical tolerance used in root finding, the default providing (at least) four significant digits. |

## Details

Exactly one of the parameters n, delta, power, sd1, sd2 and sig.level must be passed as NULL, and that parameter is determined from the others. Notice that the last three have non-NULL defaults, so NULL must be explicitly passed if you want to compute them.

If strict = TRUE is used, the power will include the probability of rejection in the opposite direction of the true effect, in the two-sided case. Without this the power will be half the significance level if the true difference is zero.

## Value

Object of class "power.htest", a list of the arguments (including the computed one) augmented with method and note elements.

**Note**

The function and its documentation was adapted from `power.t.test` implemented by Peter Dalggaard and based on previous work by Claus Ekstroem.

`uniroot` is used to solve the power equation for unknowns, so you may see errors from it, notably about inability to bracket the root when invalid arguments are given.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

J. Hedderich, L. Sachs. *Angewandte Statistik: Methodensammlung mit R*. Springer 2016.

**See Also**

[power.welch.t.test](#), [power.t.test](#), [t.test](#), [uniroot](#)

**Examples**

```
## more conservative than classical or Welch t-test
power.hsu.t.test(n = 20, delta = 1)
power.hsu.t.test(power = .90, delta = 1)
power.hsu.t.test(power = .90, delta = 1, alternative = "one.sided")

## sd1 = 0.5, sd2 = 1
power.welch.t.test(delta = 0.5, sd1 = 0.5, sd2 = 1, power = 0.9)
power.hsu.t.test(delta = 0.5, sd1 = 0.5, sd2 = 1, power = 0.9)

if(require(MKinfer)){
  ## empirical check
  M <- 10000
  ps <- numeric(M)
  for(i in seq_len(M)){
    x <- rnorm(55, mean = 0, sd = 0.5)
    y <- rnorm(55, mean = 0.5, sd = 1.0)
    ps[i] <- hsu.t.test(x, y)$p.value
  }
  ## empirical power
  sum(ps < 0.05)/M
}
```

---

power.mpe.atleast.one *Power for at least One Endpoint with Known Covariance*

---

### Description

The function calculates either sample size or power for continuous multiple primary endpoints for at least one endpoint with known covariance.

### Usage

```
power.mpe.atleast.one(K, n = NULL, delta = NULL, Sigma, SD, rho, sig.level = 0.05/K,
  power = NULL, n.max = 1e5, tol = .Machine$double.eps^0.25)
```

### Arguments

|           |                                                                            |
|-----------|----------------------------------------------------------------------------|
| K         | number of endpoints                                                        |
| n         | optional: sample size                                                      |
| delta     | expected effect size                                                       |
| Sigma     | A covariance of known matrix                                               |
| SD        | known standard deviations (length K)                                       |
| rho       | known correlations (length $0.5 * K * (K - 1)$ )                           |
| sig.level | Significance level (Type I error probability)                              |
| power     | optional: Power of test (1 minus Type II error probability)                |
| n.max     | upper end of the interval to be search for n via <a href="#">uniroot</a> . |
| tol       | The desired accuracy                                                       |

### Details

The function can be used to either compute sample size or power for continuous multiple primary endpoints with known covariance where a significant difference for at least one endpoint is expected. The implementation is based on the formulas given in the references below.

The null hypothesis reads  $\mu_{Tk} - \mu_{Ck} \leq 0$  for all  $k \in \{1, \dots, K\}$  where Tk is treatment k, Ck is control k and K is the number of co-primary endpoints.

One has to specify either n or power, the other parameter is determined. Moreover, either covariance matrix Sigma or standard deviations SD and correlations rho must be given.

### Value

Object of class `power.mpe.test`, a list of arguments (including the computed one) augmented with method and note elements.

### Note

The function first appeared in package **mpe**, which is now archived on CRAN.

**Author(s)**

Srinath Kolampally, Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

Sugimoto, T. and Sozu, T. and Hamasaki, T. (2012). A convenient formula for sample size calculations in clinical trials with multiple co-primary continuous endpoints. *Pharmaceut. Statist.*, **11**: 118-128. doi:10.1002/pst.505

Sozu, T. and Sugimoto, T. and Hamasaki, T. and Evans, S.R. (2015). *Sample Size Determination in Clinical Trials with Multiple Endpoints*. Springer Briefs in Statistics, ISBN 978-3-319-22005-5.

**Examples**

```
## compute power
power.mpe.atleast.one(K = 2, delta = c(0.2,0.2), Sigma = diag(c(1,1)), power = 0.8)

## compute sample size
power.mpe.atleast.one(K = 2, delta = c(0.2,0.2), Sigma = diag(c(2,2)), power = 0.9)

## known covariance matrix
Sigma <- matrix(c(1.440, 0.840, 1.296, 0.840,
                  0.840, 1.960, 0.168, 1.568,
                  1.296, 0.168, 1.440, 0.420,
                  0.840, 1.568, 0.420, 1.960), ncol = 4)

## compute power
power.mpe.atleast.one(K = 4, n = 60, delta = c(0.5, 0.75, 0.5, 0.75), Sigma = Sigma)
## equivalent: known SDs and correlation rho
power.mpe.atleast.one(K = 4, n = 60, delta = c(0.5, 0.75, 0.5, 0.75),
                      SD = c(1.2, 1.4, 1.2, 1.4),
                      rho = c(0.5, 0.9, 0.5, 0.1, 0.8, 0.25))
```

---

power.mpe.known.var      *Multiple Co-Primary Endpoints with Known Covariance*

---

**Description**

The function calculates either sample size or power for continuous multiple co-primary endpoints with known covariance.

**Usage**

```
power.mpe.known.var(K, n = NULL, delta = NULL, Sigma, SD, rho,
                    sig.level = 0.05, power = NULL, n.max = 1e5, tol = .Machine$double.eps^0.25)
```

**Arguments**

|           |                                                                            |
|-----------|----------------------------------------------------------------------------|
| K         | number of co-primary endpoints                                             |
| n         | optional: sample size                                                      |
| delta     | expected effect size (length K)                                            |
| Sigma     | known covariance matrix (dimension K x K)                                  |
| SD        | known standard deviations (length K)                                       |
| rho       | known correlations (length $0.5 * K * (K - 1)$ )                           |
| sig.level | significance level (Type I error probability)                              |
| power     | optional: power of test (1 minus Type II error probability)                |
| n.max     | upper end of the interval to be search for n via <a href="#">uniroot</a> . |
| tol       | the desired accuracy for <a href="#">uniroot</a> .                         |

**Details**

The function can be used to either compute sample size or power for continuous multiple co-primary endpoints with known covariance where a multivariate normal distribution is assumed. The implementation is based on the formulas given in the references below.

The null hypothesis reads  $\mu_{T_k} - \mu_{C_k} \leq 0$  for at least one  $k \in \{1, \dots, K\}$  where  $T_k$  is treatment k,  $C_k$  is control k and K is the number of co-primary endpoints.

One has to specify either n or power, the other parameter is determined. Moreover, either covariance matrix Sigma or standard deviations SD and correlations rho must be given.

**Value**

Object of class `power.mpe.test`, a list of arguments (including the computed one) augmented with method and note elements.

**Note**

The function first appeared in package **mpe**, which is now archived on CRAN.

**Author(s)**

Srinath Kolampally, Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

- Sugimoto, T. and Sozu, T. and Hamasaki, T. (2012). A convenient formula for sample size calculations in clinical trials with multiple co-primary continuous endpoints. *Pharmaceut. Statist.*, **11**: 118-128. doi:10.1002/pst.505
- Sozu, T. and Sugimoto, T. and Hamasaki, T. and Evans, S.R. (2015). *Sample Size Determination in Clinical Trials with Multiple Endpoints*. Springer Briefs in Statistics, ISBN 978-3-319-22005-5.

**See Also**

[power.mpe.unknown.var](#)

## Examples

```
## compute power
power.mpe.known.var(K = 2, n = 20, delta = c(1,1), Sigma = diag(c(1,1)))

## compute sample size
power.mpe.known.var(K = 2, delta = c(1,1), Sigma = diag(c(2,2)), power = 0.9,
  sig.level = 0.025)

## known covariance matrix
Sigma <- matrix(c(1.440, 0.840, 1.296, 0.840,
  0.840, 1.960, 0.168, 1.568,
  1.296, 0.168, 1.440, 0.420,
  0.840, 1.568, 0.420, 1.960), ncol = 4)

## compute power
power.mpe.known.var(K = 4, n = 60, delta = c(0.5, 0.75, 0.5, 0.75), Sigma = Sigma)
## equivalent: known SDs and correlation rho
power.mpe.known.var(K = 4, n = 60, delta = c(0.5, 0.75, 0.5, 0.75),
  SD = c(1.2, 1.4, 1.2, 1.4),
  rho = c(0.5, 0.9, 0.5, 0.1, 0.8, 0.25))
```

---

power.mpe.unknown.var *Multiple Co-Primary Endpoints with Unknown Covariance*

---

## Description

The function calculates either sample size or power for continuous multiple co-primary endpoints with unknown covariance.

## Usage

```
power.mpe.unknown.var(K, n = NULL, delta = NULL, Sigma, SD, rho, sig.level = 0.05,
  power = NULL, M = 10000, n.min = NULL, n.max = NULL,
  tol = .Machine$double.eps^0.25, use.uniroot = TRUE)
```

## Arguments

|           |                                                             |
|-----------|-------------------------------------------------------------|
| K         | number of co-primary endpoints                              |
| n         | optional: sample size                                       |
| delta     | expected effect size (length K)                             |
| Sigma     | unknown covariance matrix (dimension K x K)                 |
| SD        | unknown standard deviations (length K)                      |
| rho       | unknown correlations (length $0.5 * K * (K - 1)$ )          |
| sig.level | significance level (Type I error probability)               |
| power     | optional: power of test (1 minus Type II error probability) |
| M         | Number of replications for the required simulations.        |

|             |                                                                         |
|-------------|-------------------------------------------------------------------------|
| n.min       | Starting point of search interval for sample size                       |
| n.max       | End point of search interval for sample size, must be larger than n.min |
| tol         | the desired accuracy for <a href="#">uniroot</a>                        |
| use.uniroot | Finds one root of one equation                                          |

## Details

The function can be used to either compute sample size or power for continuous multiple co-primary endpoints with unknown covariance. The implementation is based on the formulas given in the references below.

The null hypothesis reads  $\mu_{Tk} - \mu_{Ck} \leq 0$  for at least one  $k \in \{1, \dots, K\}$  where  $T_k$  is treatment  $k$ ,  $C_k$  is control  $k$  and  $K$  is the number of co-primary endpoints.

One has to specify either  $n$  or power, the other parameter is determined. An approach to calculate sample size  $n$ , is to first call [power.mpe.known.var](#) and use the result as  $n.min$ . The input for  $n.max$  must be larger than  $n.min$ . Moreover, either covariance matrix  $\Sigma$  or standard deviations  $SD$  and correlations  $\rho$  must be given.

The sample size is calculated by simulating Wishart distributed random matrices, hence the results include a certain random variation.

## Value

Object of class `power.mpe.test`, a list of arguments (including the computed one) augmented with method and note elements.

## Note

The function first appeared in package **mpe**, which is now archived on CRAN.

## Author(s)

Srinath Kolampally, Matthias Kohl <Matthias.Kohl@stamats.de>

## References

Sugimoto, T. and Sozu, T. and Hamasaki, T. (2012). A convenient formula for sample size calculations in clinical trials with multiple co-primary continuous endpoints. *Pharmaceut. Statist.*, **11**: 118-128. doi:10.1002/pst.505

Sozu, T. and Sugimoto, T. and Hamasaki, T. and Evans, S.R. (2015). *Sample Size Determination in Clinical Trials with Multiple Endpoints*. Springer Briefs in Statistics, ISBN 978-3-319-22005-5.

## See Also

[power.mpe.known.var](#)

## Examples

```
## compute power
## Not run:
power.mpe.unknown.var(K = 2, n = 20, delta = c(1,1), Sigma = diag(c(1,1)))

## To compute sample size, first assume covariance as known
power.mpe.known.var(K = 2, delta = c(1,1), Sigma = diag(c(2,2)), power = 0.9,
  sig.level = 0.025)

## The value of n, which is 51, is used as n.min and n.max must be larger
## then n.min so we try 60.
power.mpe.unknown.var(K = 2, delta = c(1,1), Sigma = diag(c(2,2)), power = 0.9,
  sig.level = 0.025, n.min = 51, n.max = 60)

## More complex example with unknown covariance matrix assumed to be
Sigma <- matrix(c(1.440, 0.840, 1.296, 0.840,
  0.840, 1.960, 0.168, 1.568,
  1.296, 0.168, 1.440, 0.420,
  0.840, 1.568, 0.420, 1.960), ncol = 4)

## compute power
power.mpe.unknown.var(K = 4, n = 90, delta = c(0.5, 0.75, 0.5, 0.75), Sigma = Sigma)
## equivalent: unknown SDs and correlation rho
power.mpe.unknown.var(K = 4, n = 90, delta = c(0.5, 0.75, 0.5, 0.75),
  SD = c(1.2, 1.4, 1.2, 1.4),
  rho = c(0.5, 0.9, 0.5, 0.1, 0.8, 0.25))

## End(Not run)
```

---

power.nb.test

*Power Calculation for Comparing Two Negative Binomial Rates*

---

## Description

Compute sample size or power for comparing two negative binomial rates.

## Usage

```
power.nb.test(n = NULL, mu0, mu1, RR, duration = 1, theta, ssize.ratio = 1,
  sig.level = 0.05, power = NULL, alternative = c("two.sided", "one.sided"),
  approach = 3)
```

## Arguments

|          |                                                   |
|----------|---------------------------------------------------|
| n        | Sample size for group 0 (control group).          |
| mu0      | expected rate of events per time unit for group 0 |
| mu1      | expected rate of events per time unit for group 1 |
| RR       | ratio of expected event rates: $\mu_1/\mu_0$      |
| duration | (average) treatment duration                      |

|             |                                                                                |
|-------------|--------------------------------------------------------------------------------|
| theta       | theta parameter of negative binomial distribution; see <a href="#">rnegbin</a> |
| ssize.ratio | ratio of sample sizes: $n1/n$ where $n1$ is sample size of group 1             |
| sig.level   | Significance level (Type I error probability)                                  |
| power       | Power of test (1 minus Type II error probability)                              |
| alternative | one- or two-sided test                                                         |
| approach    | 1, 2, or 3; see Zhu and Lakkis (2014).                                         |

### Details

Exactly one of the parameters `n` and `power` must be passed as `NULL`, and that parameter is determined from the other.

The computations are based on the formulas given in Zhu and Lakkis (2014). Please be careful, as we are using a slightly different parametrization ( $\theta = 1/k$ ).

Zhu and Lakkis (2014) based on their simulation studies recommend to use their approach 2 or 3.

### Value

Object of class `"power.htest"`, a list of the arguments (including the computed one) augmented with a note element.

### Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de>

### References

H. Zhu and H. Lakkis (2014). Sample size calculation for comparing two negative binomial rates. *Statistics in Medicine*, **33**:376-387.

### See Also

[rnegbin](#), [glm.nb](#)

### Examples

```
## examples from Table I in Zhu and Lakkis (2014)
## theta = 1/k, RR = rr, mu0 = r0, duration = mu_t
power.nb.test(mu0 = 0.8, RR = 0.85, theta = 1/0.4, duration = 0.75, power = 0.8, approach = 1)
power.nb.test(mu0 = 0.8, RR = 0.85, theta = 1/0.4, duration = 0.75, power = 0.8, approach = 2)
power.nb.test(mu0 = 0.8, RR = 0.85, theta = 1/0.4, duration = 0.75, power = 0.8, approach = 3)

power.nb.test(mu0 = 1.4, RR = 1.15, theta = 1/1.5, duration = 0.75, power = 0.8, approach = 1)
power.nb.test(mu0 = 1.4, RR = 1.15, theta = 1/1.5, duration = 0.75, power = 0.8, approach = 2)
power.nb.test(mu0 = 1.4, RR = 1.15, theta = 1/1.5, duration = 0.75, power = 0.8, approach = 3)

## examples from Table II in Zhu and Lakkis (2014) - seem to be total sample sizes
## can reproduce the results with mu_t = 1.0 (not 0.7!)
power.nb.test(mu0 = 2.0, RR = 0.5, theta = 1, duration = 1.0, ssize.ratio = 1,
```

```

        power = 0.8, approach = 1)
power.nb.test(mu0 = 2.0, RR = 0.5, theta = 1, duration = 1.0, ssize.ratio = 1,
              power = 0.8, approach = 2)
power.nb.test(mu0 = 2.0, RR = 0.5, theta = 1, duration = 1.0, ssize.ratio = 1,
              power = 0.8, approach = 3)

power.nb.test(mu0 = 10.0, RR = 1.5, theta = 1/5, duration = 1.0, ssize.ratio = 3/2,
              power = 0.8, approach = 1)
power.nb.test(mu0 = 10.0, RR = 1.5, theta = 1/5, duration = 1.0, ssize.ratio = 3/2,
              power = 0.8, approach = 2)
power.nb.test(mu0 = 10.0, RR = 1.5, theta = 1/5, duration = 1.0, ssize.ratio = 3/2,
              power = 0.8, approach = 3)

## examples from Table III in Zhu and Lakkis (2014)
power.nb.test(mu0 = 5.0, RR = 2.0, theta = 1/0.5, duration = 1, power = 0.8, approach = 1)
power.nb.test(mu0 = 5.0, RR = 2.0, theta = 1/0.5, duration = 1, power = 0.8, approach = 2)
power.nb.test(mu0 = 5.0, RR = 2.0, theta = 1/0.5, duration = 1, power = 0.8, approach = 3)

## examples from Table IV in Zhu and Lakkis (2014)
power.nb.test(mu0 = 5.9/3, RR = 0.4, theta = 0.49, duration = 3, power = 0.9, approach = 1)
power.nb.test(mu0 = 5.9/3, RR = 0.4, theta = 0.49, duration = 3, power = 0.9, approach = 2)
power.nb.test(mu0 = 5.9/3, RR = 0.4, theta = 0.49, duration = 3, power = 0.9, approach = 3)

power.nb.test(mu0 = 13/6, RR = 0.2, theta = 0.52, duration = 6, power = 0.9, approach = 1)
power.nb.test(mu0 = 13/6, RR = 0.2, theta = 0.52, duration = 6, power = 0.9, approach = 2)
power.nb.test(mu0 = 13/6, RR = 0.2, theta = 0.52, duration = 6, power = 0.9, approach = 3)

## see Section 5 of Zhu and Lakkis (2014)
power.nb.test(mu0 = 0.66, RR = 0.8, theta = 1/0.8, duration = 0.9, power = 0.9)

```

---

power.prop1.test

---

*Power Calculations for One-Sample Test for Proportions*


---

## Description

Compute the power of the one-sample test for proportions, or determine parameters to obtain a target power.

## Usage

```

power.prop1.test(n = NULL, p1 = NULL, p0 = 0.5, sig.level = 0.05,
                 power = NULL,
                 alternative = c("two.sided", "less", "greater"),
                 cont.corr = TRUE, tol = .Machine$double.eps^0.25)

```

**Arguments**

|             |                                                                                                     |
|-------------|-----------------------------------------------------------------------------------------------------|
| n           | number of observations (per group)                                                                  |
| p1          | expected probability                                                                                |
| p0          | probability under the null hypothesis                                                               |
| sig.level   | significance level (Type I error probability)                                                       |
| power       | power of test (1 minus Type II error probability)                                                   |
| alternative | one- or two-sided test. Can be abbreviated.                                                         |
| cont.corr   | use continuity correction                                                                           |
| tol         | numerical tolerance used in root finding, the default providing (at least) four significant digits. |

**Details**

Exactly one of the parameters `n`, `p1`, `power`, and `sig.level` must be passed as `NULL`, and that parameter is determined from the others. Notice that `sig.level` has a non-`NULL` default so `NULL` must be explicitly passed if you want it computed.

The computation is based on the asymptotic formulas provided in Section 2.5.1 of Fleiss et al. (2003). If `cont.corr = TRUE` a continuity correction is applied, which may lead to better approximations of the finite-sample values.

**Value**

Object of class `"power.htest"`, a list of the arguments (including the computed one) augmented with `method` and `note` elements.

**Note**

The documentation was adapted from [power.prop.test](#).

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

J.L. Fleiss, B. Levin and M.C. Paik (2003). *Statistical Methods for Rates and Proportions*. Wiley Series in Probability and Statistics.

**See Also**

[power.prop.test](#), [prop.test](#)

**Examples**

```

power.prop1.test(p1 = 0.4, power = 0.8)
power.prop1.test(p1 = 0.4, power = 0.8, cont.corr = FALSE)
power.prop1.test(p1 = 0.6, power = 0.8)
power.prop1.test(n = 204, power = 0.8)
power.prop1.test(n = 204, p1 = 0.4, power = 0.8, sig.level = NULL)
power.prop1.test(n = 194, p1 = 0.4, power = 0.8, sig.level = NULL,
  cont.corr = FALSE)

power.prop1.test(p1 = 0.1, p0 = 0.3, power = 0.8, alternative = "less")
power.prop1.test(p1 = 0.1, p0 = 0.3, power = 0.8, alternative = "less",
  cont.corr = FALSE)
power.prop1.test(n = 31, p0 = 0.3, power = 0.8, alternative = "less")
power.prop1.test(n = 31, p1 = 0.1, p0 = 0.3, power = 0.8, sig.level = NULL,
  alternative = "less")

power.prop1.test(p1 = 0.5, p0 = 0.3, power = 0.8, alternative = "greater")
power.prop1.test(p1 = 0.5, p0 = 0.3, power = 0.8, alternative = "greater",
  cont.corr = FALSE)
power.prop1.test(n = 40, p0 = 0.3, power = 0.8, alternative = "greater")
power.prop1.test(n = 40, p1 = 0.5, p0 = 0.3, power = 0.8, sig.level = NULL,
  alternative = "greater")

```

---

power.welch.t.test      *Power Calculations for Two-sample Welch t Test*

---

**Description**

Compute the power of the two-sample Welch t test, or determine parameters to obtain a target power.

**Usage**

```

power.welch.t.test(n = NULL, delta = NULL, sd1 = 1, sd2 = 1, sig.level = 0.05,
  power = NULL, alternative = c("two.sided", "one.sided"),
  strict = FALSE, tol = .Machine$double.eps^0.25)

```

**Arguments**

|             |                                                   |
|-------------|---------------------------------------------------|
| n           | number of observations (per group)                |
| delta       | (expected) true difference in means               |
| sd1         | (expected) standard deviation of group 1          |
| sd2         | (expected) standard deviation of group 2          |
| sig.level   | significance level (Type I error probability)     |
| power       | power of test (1 minus Type II error probability) |
| alternative | one- or two-sided test. Can be abbreviated.       |

|                     |                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------|
| <code>strict</code> | use strict interpretation in two-sided case                                                         |
| <code>tol</code>    | numerical tolerance used in root finding, the default providing (at least) four significant digits. |

### Details

Exactly one of the parameters `n`, `delta`, `power`, `sd1`, `sd2` and `sig.level` must be passed as `NULL`, and that parameter is determined from the others. Notice that the last three have non-`NULL` defaults, so `NULL` must be explicitly passed if you want to compute them.

If `strict = TRUE` is used, the power will include the probability of rejection in the opposite direction of the true effect, in the two-sided case. Without this the power will be half the significance level if the true difference is zero.

### Value

Object of class `"power.htest"`, a list of the arguments (including the computed one) augmented with method and note elements.

### Note

The function and its documentation was adapted from `power.t.test` implemented by Peter Dalggaard and based on previous work by Claus Ekstroem.

`uniroot` is used to solve the power equation for unknowns, so you may see errors from it, notably about inability to bracket the root when invalid arguments are given.

### Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de>

### References

S.L. Jan and G. Shieh (2011). Optimal sample sizes for Welch's test under various allocation and cost considerations. *Behav Res Methods*, 43, 4:1014-22.

### See Also

[power.t.test](#), [t.test](#), [uniroot](#)

### Examples

```
## identical results as power.t.test, since sd = sd1 = sd2 = 1
power.welch.t.test(n = 20, delta = 1)
power.welch.t.test(power = .90, delta = 1)
power.welch.t.test(power = .90, delta = 1, alternative = "one.sided")

## sd1 = 0.5, sd2 = 1
power.welch.t.test(delta = 2, sd1 = 0.5, sd2 = 1, power = 0.9)

## empirical check
```

```

M <- 10000
pvals.welch <- numeric(M)
for(i in seq_len(M)){
  x <- rnorm(5, mean = 0, sd = 0.5)
  y <- rnorm(5, mean = 2, sd = 1.0)
  pvals.welch[i] <- t.test(x, y)$p.value
}
## empirical power
sum(pvals.welch < 0.05)/M

```

---

print.power.mpe.test    *Print Methods for Hypothesis Tests, Sample size and Power Calculations*

---

## Description

Printing objects of class "power.mpe.test" by simple [print](#) methods.

## Usage

```

## S3 method for class 'power.mpe.test'
print(x, digits = getOption("digits"), ...)

```

## Arguments

|        |                                                    |
|--------|----------------------------------------------------|
| x      | object of class "power.mpe.test".                  |
| digits | number of significant digits to be used.           |
| ...    | further arguments to be passed to or from methods. |

## Details

The print method is based on the respective method print.power.htest of package **stats**.

A power.mpe.test object is just a named list of numbers and character strings, supplemented with method and note elements. The method is displayed as a title, the note as a footnote, and the remaining elements are given in an aligned 'name = value' format.

## Value

the argument x, invisibly, as for all [print](#) methods.

## Note

The function first appeared in package **mpe**, which is now archived on CRAN.

## Author(s)

Srinath Kolampally, Matthias Kohl <Matthias.Kohl@stamats.de>

**See Also**

[print.power.htest](#), [power.mpe.known.var](#), [power.mpe.unknown.var](#)

**Examples**

```
(pkv <- power.mpe.known.var(K = 2, delta = c(1,1), Sigma = diag(c(2,2)), power = 0.9,
                           sig.level = 0.025))
print(pkv, digits = 4) # using less digits than default
print(pkv, digits = 12) # using more digits than default
```

---

qqunif

*qq-Plots for Uniform Distribution*


---

**Description**

Produce qq-plot(s) of the given effect size and p values assuming a uniform distribution.

**Usage**

```
qqunif(x, ...)

## Default S3 method:
qqunif(x, min = 0, max = 1, ...)

## S3 method for class 'sim.power.ttest'
qqunif(x, color.line = "orange", shape = 19, size = 1,
       alpha = 1, ...)

## S3 method for class 'sim.power.wtest'
qqunif(x, color.line = "orange", shape = 19, size = 1,
       alpha = 1, ...)
```

**Arguments**

|            |                                                        |
|------------|--------------------------------------------------------|
| x          | numeric vector or data (object).                       |
| min        | single numeric, lower limit of the distribution.       |
| max        | single numeric, upper limit of the distribution.       |
| color.line | color of the line indicating the uniform distribution. |
| shape      | point shape.                                           |
| size       | point size.                                            |
| alpha      | blending factor (default: no blending).                |
| ...        | further arguments that may be passed through).         |

**Details**

The plot generates a ggplot2 object that is shown.

Missing values are handled by the ggplot2 functions.

**Value**

Object of class gg and ggplot.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**Examples**

```
## default
qqunif(runif(100))

## visualization of empirical power and type-I-error
res1 <- sim.power.t.test(nx = 5, rx = rnorm, rx.H0 = rnorm,
                        ny = 10, ry = function(x) rnorm(x, mean = 3, sd = 3),
                        ry.H0 = function(x) rnorm(x, sd = 3))
qqunif(res1, alpha = 0.1)

res2 <- sim.power.wilcox.test(nx = 6, rx = rnorm, rx.H0 = rnorm,
                             ny = 6, ry = function(x) rnorm(x, mean = 2),
                             ry.H0 = rnorm)
qqunif(res2)
```

---

sim.power.t.test

*Monte Carlo Simulations for Empirical Power of Two-sample t-Tests*

---

**Description**

Simulate the empirical power and type-I-error of two-sample t-tests; i.e., classical (equal variances), Welch and Hsu t-tests.

**Usage**

```
sim.power.t.test(nx, rx, rx.H0 = NULL, ny, ry, ry.H0 = NULL,
                 sig.level = 0.05, conf.int = FALSE, mu = 0,
                 alternative = c("two.sided", "less", "greater"),
                 iter = 10000)
```

**Arguments**

|                          |                                                                              |
|--------------------------|------------------------------------------------------------------------------|
| <code>nx</code>          | single numeric, sample size of first group.                                  |
| <code>rx</code>          | function to simulate the values of first group (assuming H1).                |
| <code>rx.H0</code>       | NULL or function to simulate the values of first group (assuming H0).        |
| <code>ny</code>          | single numeric, sample size of second group.                                 |
| <code>ry</code>          | function to simulate the values of second group (assuming H1).               |
| <code>ry.H0</code>       | NULL or function to simulate the values of second group (assuming H0).       |
| <code>sig.level</code>   | significance level (type I error probability)                                |
| <code>conf.int</code>    | logical, shall confidence intervals be computed. Increases computation time! |
| <code>mu</code>          | true value of the location shift for the null hypothesis.                    |
| <code>alternative</code> | one- or two-sided test. Can be abbreviated.                                  |
| <code>iter</code>        | single integer, number of iterations of the simulations.                     |

**Details**

Functions `rx` and `ry` are used to simulate the data under the alternative hypothesis H1. If specified, functions `rx.H0` and `ry.H0` simulate the data under the null hypothesis H0.

For fast computations functions from package `matrixTests` are used.

**Value**

Object of class "`sim.power.t.test`" with the results of the three t-tests in the list elements `Classical`, `Welch` and `Hsu`. In addition, the simulation setup is saved in element `SetUp`.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

- J. Hedderich, L. Sachs. *Angewandte Statistik: Methodensammlung mit R*. Springer 2018.
- Hsu, P. (1938). Contribution to the theory of "student's" t-test as applied to the problem of two samples. *Statistical Research Memoirs* **2**: 1-24.
- Student (1908). The Probable Error of a Mean. *Biometrika*, **6**(1): 1-25.
- Welch, B. L. (1947). The generalization of "Student's" problem when several different population variances are involved. *Biometrika*, **34** (1-2): 28-35.

**See Also**

[t.test](#), [hsu.t.test](#), [ttest](#)

**Examples**

```

## Equal variance, small sample size
power.t.test(n = 5, delta = 2)
power.welch.t.test(n = 5, delta = 2)
power.hsu.t.test(n = 5, delta = 2)
sim.power.t.test(nx = 5, rx = rnorm, rx.H0 = rnorm,
                 ny = 5, ry = function(x) rnorm(x, mean = 2), ry.H0 = rnorm)

## Equal variance, moderate sample size
power.t.test(n = 25, delta = 0.8)
power.welch.t.test(n = 25, delta = 0.8)
power.hsu.t.test(n = 25, delta = 0.8)
sim.power.t.test(nx = 25, rx = rnorm, rx.H0 = rnorm,
                 ny = 25, ry = function(x) rnorm(x, mean = 0.8), ry.H0 = rnorm)

## Equal variance, high sample size
power.t.test(n = 100, delta = 0.4)
power.welch.t.test(n = 100, delta = 0.4)
power.hsu.t.test(n = 100, delta = 0.4)
sim.power.t.test(nx = 100, rx = rnorm, rx.H0 = rnorm,
                 ny = 100, ry = function(x) rnorm(x, mean = 0.4), ry.H0 = rnorm)

## Unequal variance, small sample size
power.welch.t.test(n = 5, delta = 5, sd1 = 1, sd2 = 3)
power.hsu.t.test(n = 5, delta = 5, sd1 = 1, sd2 = 3)
sim.power.t.test(nx = 5, rx = rnorm, rx.H0 = rnorm,
                 ny = 5, ry = function(x) rnorm(x, mean = 5, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))

## Unequal variance, moderate sample size
power.welch.t.test(n = 25, delta = 1.8, sd1 = 1, sd2 = 3)
power.hsu.t.test(n = 25, delta = 1.8, sd1 = 1, sd2 = 3)
sim.power.t.test(nx = 25, rx = rnorm, rx.H0 = rnorm,
                 ny = 25, ry = function(x) rnorm(x, mean = 1.8, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))

## Unequal variance, high sample size
power.welch.t.test(n = 100, delta = 0.9, sd1 = 1, sd2 = 3)
power.hsu.t.test(n = 100, delta = 0.9, sd1 = 1, sd2 = 3)
sim.power.t.test(nx = 100, rx = rnorm, rx.H0 = rnorm,
                 ny = 100, ry = function(x) rnorm(x, mean = 0.9, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))

## Unequal variance, unequal sample sizes
## small sample sizes
sim.power.t.test(nx = 10, rx = rnorm, rx.H0 = rnorm,
                 ny = 5, ry = function(x) rnorm(x, mean = 5, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))
sim.power.t.test(nx = 5, rx = rnorm, rx.H0 = rnorm,
                 ny = 10, ry = function(x) rnorm(x, mean = 3, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))

```

```
## Unequal variance, unequal sample sizes
## moderate sample sizes
sim.power.t.test(nx = 25, rx = rnorm, rx.H0 = rnorm,
                 ny = 50, ry = function(x) rnorm(x, mean = 1.5, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))

## Unequal variance, unequal sample sizes
## high sample sizes
sim.power.t.test(nx = 100, rx = rnorm, rx.H0 = rnorm,
                 ny = 200, ry = function(x) rnorm(x, mean = 0.6, sd = 3),
                 ry.H0 = function(x) rnorm(x, sd = 3))
```

---

sim.power.wilcox.test *Monte Carlo Simulations for Empirical Power of Wilcoxon-Mann-Whitney Tests*

---

## Description

Simulate the empirical power and type-I-error of Wilcoxon-Mann-Whitney tests.

## Usage

```
sim.power.wilcox.test(nx, rx, rx.H0 = NULL, ny, ry, ry.H0 = NULL,
                     alternative = c("two.sided", "less", "greater"),
                     sig.level = 0.05, conf.int = FALSE, approximate = FALSE,
                     ties = FALSE, iter = 10000, nresample = 10000,
                     parallel = "no", ncpus = 1L, cl = NULL)
```

## Arguments

|                          |                                                                                                                 |
|--------------------------|-----------------------------------------------------------------------------------------------------------------|
| <code>nx</code>          | single numeric, sample size of first group.                                                                     |
| <code>rx</code>          | function to simulate the values of first group (assuming H1).                                                   |
| <code>rx.H0</code>       | NULL or function to simulate the values of first group (assuming H0).                                           |
| <code>ny</code>          | single numeric, sample size of second group.                                                                    |
| <code>ry</code>          | function to simulate the values of second group (assuming H1).                                                  |
| <code>ry.H0</code>       | NULL or function to simulate the values of second group (assuming H0).                                          |
| <code>alternative</code> | one- or two-sided test. Can be abbreviated.                                                                     |
| <code>sig.level</code>   | significance level (type I error probability)                                                                   |
| <code>conf.int</code>    | logical, shall confidence intervals be computed. Strongly increases computation time!                           |
| <code>approximate</code> | logical, shall an approximate test be computed; see <a href="#">LocationTests</a> . Increases computation time! |
| <code>ties</code>        | logical, indicating whether ties may occur. Increases computation time!                                         |
| <code>iter</code>        | single positive integer, number of iterations of the simulations.                                               |

|           |                                                                                                                                                                            |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| nresample | single positive integer, the number of Monte Carlo replicates used for the computation of the approximative reference distribution; see <a href="#">NullDistribution</a> . |
| parallel  | a character, the type of parallel operation: either "no" (default), "multicore" or "snow"; see <a href="#">NullDistribution</a> .                                          |
| ncpus     | a single integer, the number of processes to be used in parallel operation. Defaults to 1L; see <a href="#">NullDistribution</a> .                                         |
| cl        | an object inheriting from class "cluster", specifying an optional parallel or snow cluster if parallel = "snow". Defaults to NULL; see <a href="#">NullDistribution</a> .  |

### Details

Functions rx and ry are used to simulate the data under the alternative hypothesis H1. If specified, functions rx.H0 and ry.H0 simulate the data under the null hypothesis H0.

For fast computations functions from package `matrixTests` and package `coin` are used.

### Value

Object of class "sim.power.wtest" with the results of the Wilcoxon-Mann-Whitney tests. A list elements Exact, Asymptotic and Approximate. In addition, the simulation setup is saved in element Setup.

### Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de>

### References

Mann, H and Withney, D (1947). On a test of whether one of two random variables is stochastically larger than the other. *Annals of mathematical Statistics*, **18**, 50-60.

Wilcoxon, F (1945). Individual Comparisons by Ranking Methods. *Biometrics Bulletin*, **1**, 80-83.

### See Also

[wilcox.test](#), [LocationTests](#), [wilcoxon](#)

### Examples

```
## Equal variance, small sample size
power.t.test(n = 5, power = 0.8)
sim.ssize.wilcox.test(rx = rnorm, ry = function(x) rnorm(x, mean = 2),
                      power = 0.8, n.min = 3, n.max = 10, step.size = 1)
sim.power.wilcox.test(nx = 6, rx = rnorm, rx.H0 = rnorm,
                      ny = 6, ry = function(x) rnorm(x, mean = 2),
                      ry.H0 = rnorm)
```

---

sim.ssize.wilcox.test *Sample Size for Wilcoxon Rank Sum and Signed Rank Tests*

---

## Description

Simulate the empirical power of Wilcoxon rank sum and signed rank tests for computing the required sample size.

## Usage

```
sim.ssize.wilcox.test(rx, ry = NULL, mu = 0, sig.level = 0.05, power = 0.8,
  type = c("two.sample", "one.sample", "paired"),
  alternative = c("two.sided", "less", "greater"),
  n.min = 10, n.max = 200, step.size = 10,
  iter = 10000, BREAK = TRUE, exact = NA, correct = TRUE)
```

## Arguments

|             |                                                                                                                                                                                                                                          |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rx          | function to simulate the values of x, respectively x-y in the paired case.                                                                                                                                                               |
| ry          | function to simulate the values of y in the two-sample case                                                                                                                                                                              |
| mu          | true values of the location shift for the null hypothesis.                                                                                                                                                                               |
| sig.level   | significance level (Type I error probability)                                                                                                                                                                                            |
| power       | two-sample, one-sample or paired test                                                                                                                                                                                                    |
| type        | one- or two-sided test. Can be abbreviated.                                                                                                                                                                                              |
| alternative | one- or two-sided test. Can be abbreviated.                                                                                                                                                                                              |
| n.min       | integer, start value of grid search.                                                                                                                                                                                                     |
| n.max       | integer, stop value of grid search.                                                                                                                                                                                                      |
| step.size   | integer, step size used in the grid search.                                                                                                                                                                                              |
| iter        | integer, number of iterations of the simulations.                                                                                                                                                                                        |
| BREAK       | logical, grid search stops when the empirical power is larger than the requested power.                                                                                                                                                  |
| exact       | logical or NA (default) indicator whether an exact p-value should be computed (see Details at <a href="#">wilcoxon</a> ). A single value or a logical vector with values for each observation.                                           |
| correct     | logical indicator whether continuity correction should be applied in the cases where p-values are obtained using normal approximation. A single value or logical vector with values for each observation; see <a href="#">wilcoxon</a> . |

## Details

Functions `rx` and `ry` are used to simulate the data and functions `row_wilcoxon_twosample` and `row_wilcoxon_onesample` of package **matrixTests** are used to efficiently compute the p values of the respective test.

We recommend a two steps procedure: In the first step, start with a wide grid and find out in which range of sample size values the intended power will be achieved. In the second step, the interval identified in the first step is used to find the sample size that leads to the required power setting `step.size = 1` and `BREAK = FALSE`. This approach is applied in the examples below.

## Value

Object of class `"power.htest"`, a list of the arguments (including the computed one) augmented with method and note elements.

## Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de>

## References

Wilcoxon, F (1945). Individual Comparisons by Ranking Methods. *Biometrics Bulletin*, **1**, 80-83.

## See Also

[wilcox.test](#), [wilcoxon](#)

## Examples

```
#####
## two-sample
## iter = 1000 to reduce check time
#####
rx <- function(n) rnorm(n, mean = 0, sd = 1)
ry <- function(n) rnorm(n, mean = 0.5, sd = 1)
sim.ssize.wilcox.test(rx = rx, ry = ry, n.max = 100, iter = 1000)
sim.ssize.wilcox.test(rx = rx, ry = ry, n.min = 65, n.max = 70, step.size = 1,
                      iter = 1000, BREAK = FALSE)

## compared to
power.t.test(delta = 0.5, power = 0.8)

rx <- function(n) rnorm(n, mean = 0, sd = 1)
ry <- function(n) rnorm(n, mean = 0.5, sd = 1.5)
sim.ssize.wilcox.test(rx = rx, ry = ry, n.max = 100, iter = 1000, alternative = "less")
sim.ssize.wilcox.test(rx = rx, ry = ry, n.min = 85, n.max = 90, step.size = 1,
                      iter = 1000, BREAK = FALSE, alternative = "less")

## compared to
power.welch.t.test(delta = 0.5, sd = 1, sd2 = 1.5, power = 0.8, alternative = "one.sided")

rx <- function(n) rnorm(n, mean = 0.5, sd = 1)
ry <- function(n) rnorm(n, mean = 0, sd = 1)
sim.ssize.wilcox.test(rx = rx, ry = ry, n.max = 100, iter = 1000, alternative = "greater")
```

```

sim.ssize.wilcox.test(rx = rx, ry = ry, n.min = 50, n.max = 55, step.size = 1,
                      iter = 1000, BREAK = FALSE, alternative = "greater")
## compared to
power.t.test(delta = 0.5, power = 0.8, alternative = "one.sided")

rx <- function(n) rgamma(n, scale = 10, shape = 1)
ry <- function(n) rgamma(n, scale = 15, shape = 1)
sim.ssize.wilcox.test(rx = rx, ry = ry, n.max = 200, iter = 1000)
sim.ssize.wilcox.test(rx = rx, ry = ry, n.min = 125, n.max = 135, step.size = 1,
                      iter = 1000, BREAK = FALSE)

#####
## one-sample
## iter = 1000 to reduce check time
#####
rx <- function(n) rnorm(n, mean = 0.5, sd = 1)
sim.ssize.wilcox.test(rx = rx, mu = 0, type = "one.sample", n.max = 100, iter = 1000)
sim.ssize.wilcox.test(rx = rx, mu = 0, type = "one.sample", n.min = 33, n.max = 38,
                      step.size = 1, iter = 1000, BREAK = FALSE)
## compared to
power.t.test(delta = 0.5, power = 0.8, type = "one.sample")

sim.ssize.wilcox.test(rx = rx, mu = 0, type = "one.sample", n.max = 100, iter = 1000,
                      alternative = "greater")
sim.ssize.wilcox.test(rx = rx, mu = 0, type = "one.sample", n.min = 25, n.max = 30,
                      step.size = 1, iter = 1000, BREAK = FALSE, alternative = "greater")
## compared to
power.t.test(delta = 0.5, power = 0.8, type = "one.sample", alternative = "one.sided")

sim.ssize.wilcox.test(rx = rx, mu = 1, type = "one.sample", n.max = 100, iter = 1000,
                      alternative = "less")
sim.ssize.wilcox.test(rx = rx, mu = 1, type = "one.sample", n.min = 20, n.max = 30,
                      step.size = 1, iter = 1000, BREAK = FALSE, alternative = "less")
## compared to
power.t.test(delta = 0.5, power = 0.8, type = "one.sample", alternative = "one.sided")

rx <- function(n) rgamma(n, scale = 10, shape = 1)
sim.ssize.wilcox.test(rx = rx, mu = 5, type = "one.sample", n.max = 200, iter = 1000)
sim.ssize.wilcox.test(rx = rx, mu = 5, type = "one.sample", n.min = 40, n.max = 50,
                      step.size = 1, iter = 1000, BREAK = FALSE)

#####
## paired
## identical to one-sample, requires random number generating function
## that simulates the difference x-y
## iter = 1000 to reduce check time
#####
rxy <- function(n) rnorm(n, mean = 0.5, sd = 1)
sim.ssize.wilcox.test(rx = rxy, mu = 0, type = "paired", n.max = 100,
                      iter = 1000)
sim.ssize.wilcox.test(rx = rxy, mu = 0, type = "paired", n.min = 33,
                      n.max = 38, step.size = 1, iter = 1000, BREAK = FALSE)
## compared to

```

```
power.t.test(delta = 0.5, power = 0.8, type = "paired")
```

---

|              |                                         |
|--------------|-----------------------------------------|
| ssize.auc.ci | <i>Sample Size Calculations for AUC</i> |
|--------------|-----------------------------------------|

---

**Description**

Compute sample size, power, delta, or significance level of a diagnostic test for an expected AUC.

**Usage**

```
ssize.auc.ci(AUC = NULL, delta = NULL, n = NULL, sig.level = 0.05,  
             power = NULL, prev = NULL, NMAX = 1e4)
```

**Arguments**

|           |                                                                                       |
|-----------|---------------------------------------------------------------------------------------|
| AUC       | Expected AUC.                                                                         |
| n         | Total sample size (number of cases + number of controls).                             |
| delta     | AUC-delta is used as lower confidence limit                                           |
| sig.level | Significance level (Type I error probability)                                         |
| power     | Assurance probability of confidence interval (1 minus Type II error probability)      |
| prev      | Expected prevalence, if NULL prevalence is ignored which means prev = 0.5 is assumed. |
| NMAX      | Maximum sample size considered.                                                       |

**Details**

Exactly one of the parameters n, delta, sig.level, and power must be passed as NULL, and that parameter is determined from the others. Notice that sig.level has a non-NULL default so NULL must be explicitly passed if you want to compute it.

The computations use the variance of the AUC derived by Hanley and McNeil (1982) and incorporate an additional assurance probability (power) as in the approach of Flahault et al. (2005); see also Kohl and Muench (2024).

**Value**

Object of class "power.htest", a list of the arguments (including the computed one) augmented with method and note elements.

**Note**

uniroot is used to solve the equations for unknowns, so you may see errors from it, notably about inability to bracket the root when invalid arguments are given.

Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de>

References

A. Flahault, M. Cadilhac, and G. Thomas (2005). Sample size calculation should be performed for design accuracy in diagnostic test studies. *Journal of Clinical Epidemiology*, **58**(8):859-862.

J.A. Hanley, B.J. McNeil (1982). The meaning and use of the area under a receiver operating characteristic (ROC) curve. *Radiology*, **143**(1):29-36.

M. Kohl, F. Muench (2024). Statistik Teil 12: Fallzahlplanung. *Die Perfusion*, **2024**(4):124-127.

See Also

[uniroot](#)

Examples

```
## compute n
ssize.auc.ci(AUC = 0.9, delta = 0.05, power = 0.8)
## compute delta
ssize.auc.ci(AUC = 0.9, n = 254, power = 0.8)
## compute power
ssize.auc.ci(AUC = 0.9, n = 254, delta = 0.05)
## compute sig.level
ssize.auc.ci(AUC = 0.9, n = 254, delta = 0.05, power = 0.8, sig.level = NULL)
```

---

|           |                                                                                    |
|-----------|------------------------------------------------------------------------------------|
| ssize.pcc | <i>Sample Size Planning for Developing Classifiers Using High Dimensional Data</i> |
|-----------|------------------------------------------------------------------------------------|

---

Description

Calculate sample size for training set in developing classifiers using high dimensional data. The calculation is based on the probability of correct classification (PCC).

Usage

```
ssize.pcc(gamma, stdFC, prev = 0.5, nrFeatures, sigFeatures = 20, verbose = FALSE)
```

Arguments

- |            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| gamma      | tolerance between PCC(infty) and PCC(n).                                                                     |
| stdFC      | expected standardized fold-change; that is, expected fold-change divided by within class standard deviation. |
| prev       | expected prevalence.                                                                                         |
| nrFeatures | number of features (variables) considered.                                                                   |

|             |                                                                                              |
|-------------|----------------------------------------------------------------------------------------------|
| sigFeatures | number of significant features; default (20) should be sufficient for most if not all cases. |
| verbose     | print intermediate results.                                                                  |

### Details

The computations are based the algorithm provided in Section~4.2 of Dobbin and Simon (2007). Prevalence is incorporated by the simple rough approach given in Section~4.4 (ibid.).

The results for prevalence equal to 50% are identical to the numbers computed by <https://brb.nci.nih.gov/brb/sampleSize/sampleSize4GE.html>. For other prevalences the numbers differ and are larger for our implementation.

### Value

Object of class "power.htest", a list of the arguments (including the computed one) augmented with method and note elements.

### Note

optimize is used to solve equation (4.3) of Dobbin and Simon (2007), so you may see errors from it.

### Author(s)

Matthias Kohl <Matthias.Kohl@stamats.de>

### References

K. Dobbin and R. Simon (2007). Sample size planning for developing classifiers using high-dimensional DNA microarray data. *Biostatistics*, **8**(1):101-117.

K. Dobbin, Y. Zhao, R. Simon (2008). How Large a Training Set is Needed to Develop a Classifier for Microarray Data? *Clin Cancer Res.*, **14**(1):108-114.

### See Also

[optimize](#)

### Examples

```
## see Table 2 of Dobbin et al. (2008)
g <- 0.1
fc <- 1.6
ssize.pcc(gamma = g, stdFC = fc, nrFeatures = 22000)

## see Table 3 of Dobbin et al. (2008)
g <- 0.05
fc <- 1.1
ssize.pcc(gamma = g, stdFC = fc, nrFeatures = 22000)
```

ssize.propCI

*Sample Size Calculation for Confidence Interval of a Proportion***Description**

Compute the sample size for the two-sided confidence interval of a single proportion.

**Usage**

```
ssize.prop.ci(prop, width, conf.level = 0.95, method = "wald-cc")
```

```
ssize.propCI(prop, width, conf.level = 0.95, method = "wald-cc")
```

**Arguments**

|            |                                                              |
|------------|--------------------------------------------------------------|
| prop       | expected proportion                                          |
| width      | width of the confidence interval                             |
| conf.level | confidence level                                             |
| method     | method used to compute the confidence interval; see Details. |

**Details**

The computation is based on the asymptotic formulas provided in Section 2.5.2 of Fleiss et al. (2003). If method = "wald-cc" a continuity correction is applied.

There are also methods for Jeffreys, Clopper-Pearson, Wilson and the Agresti-Coull interval; see also [binomCI](#).

**Value**

Object of class "power.htest", a list of the arguments (including the computed one) augmented with method and note elements.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

J.L. Fleiss, B. Levin and M.C. Paik (2003). *Statistical Methods for Rates and Proportions*. Wiley Series in Probability and Statistics.

W.W. Piegorsch (2004). Sample sizes for improved binomial confidence intervals. *Computational Statistics & Data Analysis*, **46**, 309-316.

M. Thulin (2014). The cost of using exact confidence intervals for a binomial proportion. *Electronic Journal of Statistics*, **8**(1), 817-840.

**See Also**

[power.prop1.test](#), [binomCI](#)

**Examples**

```
ssize.propCI(prop = 0.1, width = 0.1)
ssize.propCI(prop = 0.3, width = 0.1)
ssize.propCI(prop = 0.3, width = 0.1, method = "wald")
ssize.propCI(prop = 0.3, width = 0.1, method = "jeffreys")
ssize.propCI(prop = 0.3, width = 0.1, method = "clopper-pearson")
ssize.propCI(prop = 0.3, width = 0.1, method = "wilson")
ssize.propCI(prop = 0.3, width = 0.1, method = "agresti-coull")
```

---

ssize.reference.range *Power Calculations for Two-sample Hsu t Test*

---

**Description**

Compute the sample size for reference range studies, or determine parameters for a given sample size; see Jennen-Steinmetz and Wellek (2005).

**Usage**

```
ssize.reference.range(n = NULL, delta = NULL, ref.prob = 0.95, conf.prob = NULL,
  alternative = c("two.sided", "one.sided"),
  method = "parametric", exact = TRUE,
  tol = .Machine$double.eps^0.5)
```

**Arguments**

|             |                                                                                                                              |
|-------------|------------------------------------------------------------------------------------------------------------------------------|
| n           | number of observations                                                                                                       |
| delta       | difference between empirical and target coverage of reference range                                                          |
| ref.prob    | target coverage of reference range                                                                                           |
| conf.prob   | confidence probability to achieve given difference between empirical and target coverage                                     |
| alternative | a character string specifying "two.sided" (default), or one-sided reference ranges. You can specify just the initial letter. |
| method      | either "parametric" or "nonparametric"; see details                                                                          |
| exact       | use exact or approximate method                                                                                              |
| tol         | numerical tolerance used in root finding, the default providing (at least) eight significant digits.                         |



```

ssize.reference.range(delta = 0.025, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.025, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.025, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.02, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
## 314 vs. 305 (error Table 1?)
ssize.reference.range(delta = 0.02, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.02, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.02, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.015, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.015, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.015, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.015, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.01, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.01, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.01, ref.prob = 0.9, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.01, ref.prob = 0.9, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.015, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.015, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.015, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.015, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.0125, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.0125, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.0125, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.0125, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

```

```

ssize.reference.range(delta = 0.01, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.01, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.01, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.01, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.0075, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.0075, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.0075, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.0075, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

ssize.reference.range(delta = 0.005, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = TRUE)
ssize.reference.range(delta = 0.005, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE)
ssize.reference.range(delta = 0.005, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = FALSE)
ssize.reference.range(delta = 0.005, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE)

## results are equivalent to one-sided reference range with coverage of
## 95 percent instead of 90 percent; for example
ssize.reference.range(delta = 0.03, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = TRUE, alternative = "one.sided")
## 135 vs 125 (error in Table 1)
ssize.reference.range(delta = 0.03, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = TRUE, alternative = "one.sided")
ssize.reference.range(delta = 0.03, ref.prob = 0.95, conf.prob = 0.9,
  method = "parametric", exact = FALSE, alternative = "one.sided")
ssize.reference.range(delta = 0.03, ref.prob = 0.95, conf.prob = 0.9,
  method = "nonparametric", exact = FALSE, alternative = "one.sided")

```

---

volcano

---

*Volcano Plots*


---

## Description

Produce volcano plot(s) for simulations of power and type-I-error of tests.

**Usage**

```
## S3 method for class 'sim.power.ttest'
volcano(x, alpha = 1, shape = 19,
        hex = FALSE, bins = 50, ...)

## S3 method for class 'sim.power.wtest'
volcano(x, alpha = 1, shape = 19,
        hex = FALSE, bins = 50, ...)
```

**Arguments**

|       |                                                |
|-------|------------------------------------------------|
| x     | object of class <code>sim.power.ttest</code> . |
| alpha | blending factor (default: no blending).        |
| shape | point shape used.                              |
| hex   | logical, should hexagonal binning be used.     |
| bins  | number of bins used for hexagonal binning.     |
| ...   | further arguments that may be passed through). |

**Details**

The plot generates a `ggplot2` object that is shown.

Missing values are handled by the `ggplot2` functions.

**Value**

Object of class `gg` and `ggplot`.

**Author(s)**

Matthias Kohl <Matthias.Kohl@stamats.de>

**References**

Wikipedia contributors, *Volcano plot (statistics)*, Wikipedia, The Free Encyclopedia, [https://en.wikipedia.org/w/index.php?title=Volcano\\_plot\\_\(statistics\)&oldid=900217316](https://en.wikipedia.org/w/index.php?title=Volcano_plot_(statistics)&oldid=900217316) (accessed December 25, 2019).

For more sophisticated and flexible volcano plots see for instance: Blighe K, Rana S, Lewis M (2019). EnhancedVolcano: Publication-ready volcano plots with enhanced colouring and labeling. R/Bioconductor package. <https://github.com/kevinblighe/EnhancedVolcano>.

**See Also**

[volcano](#)

**Examples**

```
res1 <- sim.power.t.test(nx = 5, rx = rnorm, rx.H0 = rnorm,  
                        ny = 10, ry = function(x) rnorm(x, mean = 3, sd = 3),  
                        ry.H0 = function(x) rnorm(x, sd = 3))  
  
volcano(res1)  
  
## low number of iterations to reduce computation time  
res2 <- sim.power.wilcox.test(nx = 6, rx = rnorm, rx.H0 = rnorm,  
                             ny = 6, ry = function(x) rnorm(x, mean = 2),  
                             ry.H0 = rnorm, iter = 100, conf.int = TRUE)  
  
volcano(res2)
```

# Index

## \* **hplot**

hist, [3](#)  
qqunif, [23](#)  
volcano, [39](#)

## \* **htest**

power.ancova, [4](#)  
power.diagnostic.test, [7](#)  
power.hsu.t.test, [9](#)  
power.mpe.known.var, [12](#)  
power.mpe.unknown.var, [14](#)  
power.nb.test, [16](#)  
power.prop1.test, [18](#)  
power.welch.t.test, [20](#)  
print.power.mpe.test, [22](#)  
sim.power.t.test, [24](#)  
sim.power.wilcox.test, [27](#)  
sim.ssize.wilcox.test, [29](#)  
ssize.auc.ci, [32](#)  
ssize.pcc, [33](#)  
ssize.propCI, [35](#)  
ssize.reference.range, [36](#)

## \* **multivariate**

power.mpe.atleast.one, [11](#)  
power.mpe.known.var, [12](#)  
power.mpe.unknown.var, [14](#)

## \* **package**

MKpower-package, [2](#)

## \* **power.htest**

print.power.mpe.test, [22](#)

binomCI, [35](#), [36](#)

glm.nb, [17](#)

hist, [3](#), [3](#)

hsu.t.test, [25](#)

LocationTests, [27](#), [28](#)

MKpower (MKpower-package), [2](#)

MKpower-package, [2](#)

NullDistribution, [28](#)

optimize, [34](#)

power.ancova, [4](#)

power.anova.test, [5](#)

power.diagnostic.test, [6](#)

power.hsu.t.test, [9](#)

power.mpe.atleast.one, [11](#)

power.mpe.known.var, [12](#), [15](#), [23](#)

power.mpe.unknown.var, [13](#), [14](#), [23](#)

power.nb.test, [16](#)

power.prop.test, [19](#)

power.prop1.test, [18](#), [36](#)

power.t.test, [5](#), [10](#), [21](#)

power.welch.t.test, [10](#), [20](#)

print, [22](#)

print.power.htest, [23](#)

print.power.mpe.test, [22](#)

prop.test, [19](#)

qqunif, [23](#)

rnegbin, [17](#)

sim.power.t.test, [24](#)

sim.power.wilcox.test, [27](#)

sim.ssize.wilcox.test, [29](#)

ssize.auc.ci, [32](#)

ssize.pcc, [33](#)

ssize.prop.ci (ssize.propCI), [35](#)

ssize.propCI, [35](#)

ssize.reference.range, [36](#)

ssize.sens.ci (power.diagnostic.test), [7](#)

ssize.spec.ci (power.diagnostic.test), [7](#)

t.test, [10](#), [21](#), [25](#)

ttest, [25](#)

uniroot, [8](#), [10](#), [11](#), [13](#), [15](#), [21](#), [33](#), [37](#)

volcano, [39](#), [40](#)

wilcox.test, [28](#), [30](#)

wilcoxon, [28–30](#)